



RECOMMENDED P.C.B LAYOUT

REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2013/3/29

- 备注:
- 产品规格:
 - 1-1. 插入力: 35N MAX.
 - 1-2. 拔出力: 10N MIN. INITIAL 8-20N AFTER 3000 CYCLES
 - 1-3. 额定电流: 1.0A
 - 1-4. 额定电压: 30V
 - 1-5. 耐久性: 3000 CYCLES MIN.
 - 1-6. 耐电压: 100V AC MIN.
 - 1-7. 接触阻抗: 30mΩ MAX. INITIAL: 40mΩ MAX AFTER 3000 CYCLES
 - 1-8. 绝缘电阻: 100MΩ MIN
 - 1-9. 工作温度: -30° TO +80°

- 材质:
1. 胶芯: LCP UL94V-0
2. 2端子: C5191R-H, 镍底, 镀金G/F
3. 3外壳: SUS, 表面雾锡60μ"
4. 重点尺寸标识"▲"符号

GENERAL TOLERANCE		DWG NO.	JYSA0508-001	APPD:	WIND	Scale	1:1
X±0.45	X:±5°	Title	MICRO USB 5P/F B TYPE 180度插板有卷边	CHKD:		UNIT	mm
X±0.35	.X±2°	Part NO.	JYS-USB715-024	DR:			
XX±0.25	.XX±1°	Date	2013/03/29				
.XXX±0.15	.XXX±0.5°						
SHEET 1/1	杰宇森电子有限公司 JIE YU SEN ELECTRONIC CO., LTD.						