

RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05

REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/13

规格说明: Specifications:
电气特性: Electrical:

- 1. 额定电流: Current Rating
1.0A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
50 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level
- 5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Umate Force
Mate force: 3.0kgf (MAX)
Umate force: 0.7kgf (MIN)
- 2. 端子保持力: Terminal Retention
0.5kgf (MIN)


原材料: Material:

- 1. 塑胶: Housing:
Hing Temperature Ternmaplastics,
UI 94V-0 LCP Black
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: H 65

电镀: Finish:

- 1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 2. 外壳: Shell:
Nickel Plating (能过炉自动上锡)

GENERAL TOLERANCE		DWG NO.	APPD:	WIND	Scale	1:1
X ±0.45	X ±5°	JYSA0413-02			UNIT	mm
X ±0.35	X ±2°	TITLE	CHKD:			
XX ±0.25	.XX ±1°	MICRO USB 5P B TYPE SMT 外壳四脚全插 (有柱卷边)	DR:			
.XXX ±0.15	.xxx ±0.5°	JYS-USB715-040	Date	2012/04/13		
SHEET 1/1						

 杰宇森电子有限公司
JIE YU SEN ELECTRONIC CO., LTD.