



NOTES:

- ELECTRICAL PERFORMANCES:
 - RATING CURRENT: 3.0A
 - RATING VOLTAGE: 30V AC
 - CONTACT RESISTANCE: 40mΩ
 - INSULATION RESISTANCE: 1000 MΩ
- MECHANICAL PERFORMANCES:
 - MATING DURABILITY: 5000 CYCLES;
 - OPERATION TEMPERATURE: -40°C~+85°C.

ITEM	DESCRIPTION	MATERIAL	PLATING	Q'TY
3	SHIELD	SUS	60~120μNICKEL UNDER PLATING OVER ALL Au 10μMIN PLATING ON SMT AREA	1
2	TERMINAL	P/B	80~120μNICKEL UNDER PLATING OVER ALL: Au 1~3μMIN PLATING ON CONTACT AREA: Au 10μMIN PLATING ON SMT AREA	5
1	HOUSING	LCP	NONE	1

GENERAL TOLERANCE		DWG NO.	JYSA0508-001	APPD:	WIND	Scale	1:1
X:±0.45	X:±5°	Title	MICRO USB SPIN SMT TYPE 反向流嵌 1.45mm 互翻边 401P	CHKD:		UNIT	mm
X±0.35	X:±2°	Part NO.	JYS-USB145-046	DR:			
.XX±0.25	.XX:±1°			Date	2015/08/05		
.XXX±0.15	.xxx:±0.5°						
SHEET 1/1							

JYS 杰宇泰电子有限公司
JIE YU SEN ELECTRONIC CO., LTD.

REV.	EGN.NO.	MODIFY CONTENT	DATE
A		NEW	2015/08/05