



RECOMMENDED P.C.B LAYOUT

REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2012/04/13

规格说明: Specifications:  
电气特性: Electrical:

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf (MAX)  
Unmate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention  
1.2kgf (MIN)

原材料: Material:

1. 塑胶: Housing:  
Hing Temperature Thermoplastics,  
U1 94V-0 PBT White/Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Tails
2. 外壳: Shell:  
Nickel Plating

GENERAL TOLERANCE		DWG NO.	APPD:	WMD	Scale
X±0.45	x:±5°	JYSA0804-001			1:1
X±0.35	x:±2°	Title	USB A/F 短体10.0 全贴 卷边 6.3H	CHKD:	UNIT
.XX±0.25	.xx'±1'	Part NO.	JYS-USB630-019	DR:	mm
.XXX±0.15	.xxx'±0.5'		Date	2012/04/13	
SHEET 1/1					

杰宇森电子有限公司  
JIE YU SEN ELECTRONIC CO., LTD.